



Application Guide for Profile® Engineered Fiber Matrix™

Engineered Fiber Matrix is mixed at a rate of 60 pounds per 100 gallons of water

Engineered Fiber Matrix™ (EFM)™ has been specially designed to be mixed in a low ratio of water to product. Follow the EFM Loading Chart and Application Guide closely. Not mixing enough EFM will water-down the slurry and compromise coverage during application and the performance of the formulation.

Application / Loading Procedures

- A.** Strictly comply with equipment manufacturer's installation instructions and recommendations. Use approved hydro-spraying machines with fan-type nozzle (50-degree tip) whenever possible to achieve best soil coverage. Apply from opposing directions to assure 100% soil surface coverage. Slope interruption devices or water diversion techniques are recommended when slope lengths exceed the maximum recommendations as shown in the Slope Application and Slope Interruption Limits tables on the back page of these guidelines.
- B.** To ensure proper application rates, measure and stake area. For maximum performance, apply EFM in a two-step process:
 - 1.** Apply fertilizer with specified prescriptive solutions and typically 50% of specified seed mix with a small amount of EFM for visual metering. Do not leave seeded surfaces unprotected, especially if precipitation is imminent.
 - 2.** Mix balance of seed and **apply EFM at a rate of 60 pounds per 100 gallons (27 kg/379 liters) of water** over freshly seeded surfaces. See loading chart on the back and confirm loading rates with equipment manufacturer.²
- C.** Fill 1/3 of mechanically agitated hydroseeder with water. Turn pump on for 15 seconds and purge and pre-wet lines. Turn pump off.
- D.** Turn agitator on, open recirculation valve and load low density materials first (i.e. seed).³
- E.** Continue slowly filling tank with water while loading fiber matrix into tank.
- F.** Consult loading chart on the back to determine the number of bags to be added for desired area and application rate.
- G.** EFM should be completely loaded before water level reaches 75% of the top of tank.
- H.** Top off with water and mix until all fiber is fully broken apart and hydrated (minimum of 10 minutes – increase mixing time when applying in cold conditions). This is very important in order to fully activate the bonding additives and to obtain proper viscosity.
- I.** Add fertilizer and any other remaining amendments.
- J.** Shut off recirculation valve to minimize potential for air entrainment within the slurry.
- K.** Slow down agitator and start applying with a 50-degree fan tip nozzle.
- L.** Spray in opposing directions for maximum soil coverage.
- M.** Upon completion of application, return to water source to repeat mixing and application sequence or to flush equipment.⁴ Thoroughly purge pump and all lines of residual materials from previous load. Monitor residual material in tank after purging; excess material may reduce number of bales to be mixed in subsequent loads.

¹ Depending upon site conditions, EFM may be applied in a one-step process where all components may be mixed together in a single tank load. Consult with manufacturer for further details.

² Best results and more rapid curing are achieved at temperatures exceeding 60°F (15°C). Curing times may be accelerated in high temperature, low humidity, and windy conditions with product applied on dry soils.

³ Do not add additional tackifiers or polymers to this pre-mixed formulation.

⁴ Always flush residual slurry from hydraulic seeding/mulching equipment immediately following each application, at the end of each work period or when equipment will be left unattended; compounds containing Urea, Nitrogen, Phosphorus, Potassium and macro/micronutrients may form and can be hazardous to human health and equipment.

Loading Chart for Profile's Engineered Fiber Matrix

Tank Size (gal)	# of 50-lb bales	(lb)	Displacement (gal)	2,500 lb/ac		3,000 lb/ac		3,500 lb/ac		4,000 lb/ac	
				Sq ft	Acres	Sq ft	Acres	Sq ft	Acres	Sq ft	Acres
250	3	150	280	2,614	0.060	2,178	0.050	1,867	0.043	1,634	0.038
500	6	300	560	5,227	0.120	4,356	0.100	3,734	0.086	3,267	0.075
750	9	450	840	7,841	0.180	6,534	0.150	5,601	0.129	4,901	0.113
1,000	12	600	1,120	10,454	0.240	8,712	0.200	7,467	0.171	6,534	0.150
1,500	18	900	1,680	15,682	0.360	13,068	0.300	11,201	0.257	9,801	0.225
2,000	24	1,200	2,240	20,909	0.480	17,424	0.400	14,935	0.343	13,068	0.300
2,500	30	1,500	2,800	26,136	0.600	21,780	0.500	18,669	0.429	16,335	0.375
3,000	36	1,800	3,360	31,363	0.720	26,136	0.600	22,402	0.514	19,602	0.450
3,500	42	2,100	3,920	36,590	0.840	30,492	0.700	26,136	0.600	22,869	0.525
4,000	48	2,400	4,480	41,818	0.960	34,848	0.800	29,870	0.686	26,136	0.600

Additional Notes:

- Rough surfaces (rocky terrain, cat tracks, ripped soils, etc.) may require additional product to achieve 100% coverage.
- Be sure to allow for residual material in tank on subsequent applications.

Application Rates		
Slope Condition	English	SI
≤ 3H to 1V	3,000 lb/ac	3,360 kg/ha
> 3H to 1V and ≤ 2H to 1V	3,500 lb/ac	3,920 kg/ha
> 2H to 1V and ≤ 1H to 1V ¹	4,000 lb/ac	4,480 kg/ha
Slope Interruption Limits*		
Product Category	Length (ft)	Length (m)
EFM	50	15









For conversions:

1 lb = 0.454 kg
 1 ac = 0.41 ha
 lb/ac x 1.12 = kg/ha
 1 kg = 2.20 lb
 1 ha = 2.47 ac

¹EFM not recommended for slopes greater than 1H:1V.

*Listed slope interruption limits are for product applications on a 3H:1V slope. For application on steeper slopes, slope interruption lengths may need to be decreased.

Visual Key for Proper Application

Proper Application	Improper Application	3,000 lb/ac	3,500 lb/ac	4,000 lb/ac
				
		 } 3.4 mm thickness	 } 4.0 mm thickness	 } 4.6 mm thickness



Solutions for your Environment™

PROFILE Products LLC

750 W. Lake Cook Road • Suite 440 • Buffalo Grove, IL 60089 • 800-508-8681 • profileproducts.com

U.S. Patent #'s: 5,741,832; 5,779,782; 5,942,029; 6,158,167; 6,360,478; 7,752,804 and Patents Pending

Profile is a registered trademark of PROFILE Products LLC.

Engineered Fiber Matrix, EFM, ProMatrix, EcoMatrix and Solutions for your Environment are trademarks of PROFILE Products LLC.

EFM-01 10/19

Find us on 
facebook.com/profileEVS

PROFILE'S ENGINEERED FIBER MATRIX PRODUCTS:





DISTRIBUTED BY:

ASP Enterprises, Quick Supply Co., Bowman Construction Supply & Cascade Geosynthetics are sister companies that serve customers from the Midwest, across the Rocky Mountains to the Pacific Northwest. Together we supply customers with a variety of environmental construction materials including erosion and sediment control, geosynthetics, stormwater management, drainage products, hardscapes and outdoor living, revegetation and soil amendments, waterproofing solutions and more.



We are full line distributors of environmental construction materials for all project types. Contact us for assistance with a project or a quote on products. From specification recommendations and project development to installation and completion, we're here to help with all of your site solution needs. Our warehouses are stocked with readily available inventory and we offer same and next-day deliveries.

ASP ENTERPRISES

aspent.com

salesasp@aspent.com

ST. LOUIS

1099 Cassens Industrial Ct.
St. Louis, MO 63026
636-343-4357

KANSAS CITY

5301 E 59th St.
Kansas City, MO 64130
816-554-1191

OMAHA

15263 Cooper St.
Omaha, NE 68138
402-861-8579

WICHITA

316-393-1554

WENTZVILLE

1906 E Service Rd. HWY 61 N
Wentzville, MO 63385
636-445-9090

QUICK SUPPLY CO.

quicksupplyco.com

salesquick@quicksupplyco.com

DES MOINES

6620 NW Toni Dr.
Des Moines, IA 50313
515-289-1271

BOWMAN CONSTRUCTION SUPPLY

bowmanconstructionsupply.com

salesbcs@bowmanconstructionsupply.com

DENVER

10801 E. 54th Ave.
Denver, CO 80239
303-696-8960

COLORADO SPRINGS

2445 Wayside Ct.
Colorado Springs, CO 80915
719-257-7840

LOVELAND

4495 Woods Ave.
Loveland, CO 80538
970-535-0863

CASCADE GEOSYNTHETICS

cascadageos.com

salescascade@cascadageos.com

PORTLAND

3610 N. Suttle Rd. Bldg B
Portland, OR 97217
971-339-1020

SALT LAKE CITY

425 N. Neil Armstrong Rd.
Salt Lake City, UT 84116
435-276-0820

**GEOSYNTHETICS | EROSION CONTROL | STORMWATER MANAGEMENT
REVEGETATION & SOIL AMENDMENTS | SEDIMENT CONTROL | HARDSCAPES**