

5.0 oz Woven Needle Punched Landscape Fabric

Product Data Sheet

Fabric Properties

Typical Properties	Test Method	Unit	Roll Value
Material	-	-	polypropylene
Color	-	-	black with green lines every 12 inches
Weight	ASTM D 3776	oz/yd ²	5.0
Tensile Strength	ASTM D 4632	lbs	120 x 70
Trapezoid Tear	ASTM D 4533	lbs	40 x 35
CBR Puncture	ASTM D 6241	lbs	230
Water Flow	ASTM D 4491	gal/min/SF	10
UV Resistance	ASTM D 4355	% strength retained	>70% at 500 hours

**The above properties are typical averages.*

Available Roll Sizes

3'x50', 3'x100', 3'x250', 4'x250', 5'x250', 6'x250', 8'x250' & 12'x250'

Cascade Geosynthetics assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. Cascade Geosynthetics disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability, or fitness for a particular purpose. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The end user assumes sole responsibility for the use of this information and product.



ASP Enterprises
aspent.com
636.343.4357

Quick Supply Co.
quicksupplyco.com
515.289.1271

Bowman Construction Supply
bowmanconstructionsupply.com
303.696.8960

Cascade Geosynthetics
cascadegeos.com
971.339.1020