

HP JOINTING SAND NextGel

THE ONLY REAL NO HAZE NO DUST ALTERNATIVE



THE HIGH-PERFORMANCE JOINTING SAND VALUED BY TOP INSTALLERS

 $\mathsf{HP}\ \mathsf{NextGel}^\mathsf{TM}$ is the only true high-performance jointing sand on the market. Often imitated, the superior HP formula remains unsurpassed, both in terms of performance and ease of installation. Avoid pale imitations, always go for the original!

- For residential, commercial, industrial and public projects where mechanical compaction is possible and/or mandatory.
- Ideal for concrete, wet-cast, textured or clay pavers and porcelain tiles (only if mechanical compaction is possible)
- For false joints
- · Ideal for joints 1/16" 2" wide.
- · For high-humidity areas, heavy-sloped and high-traffic areas
- For wide joints and for all **"NO COMPACTION"** installations, you can now rely on **NOCO™** polymeric joint





3 EASY STEPS:







TIPS:

- · It is imperative to allow the installation to dry completely before installing the new jointing product.
- Temperature must be above 32 °F (0 °C) for 48 hours following installation.
- · Allow a minimum of 24-48 hours in dry conditions (depending on the overall temperature and humidity).
- A wet foundation or surface will cause the activation of the jointing product before compaction and activation. It may also clog the sides of the stones and prevent the products from filling the entire joints in depth.
- On textured pavers, use a leaf blower to blow surface water into the joints. This will remove any remaining sand and polymer residue, which will prevent hazing.
- · Refer to the complete Technical Data Sheet on techniseal.com. These are now available in ENGLISH, SPANISH and PORTUGUESE on our website.

IMPORTANT: Polymeric sand curing time after installation: **30 days.** Ensure that joint has hardened before cleaning and sealing the surface. Depending on climate and type of installation, typical recommended wait time is a minimum of 7 days after installation and may take up to 30 days.

COVERAGE: Depends on paver type and joint width. (Please see our product calculator on our website.)

MAINTENANCE:

ORGANIC WASTE MANAGEMENT

Prevent organic waste from accumulating on paver installations by regularly clearing the surface of any debris or residue using a street broom or a leaf blower. In the summer, remove cut grass from the pavers after mowing the lawn. In the fall, regularly pick up dead leaves and broken branches.

WATER AND MOISTURE MANAGEMENT

If you water your lawn with an automated sprinkler system, make sure it is calibrated properly to prevent water accumulation on the surface of paver installations, especially in shaded areas. When cleaning the pavers, don't aim the water jet directly into the joints, avoid overwatering the surface. Watering gun nozzles should be used instead of pressure washers.



Consider repositioning your roof gutter downspouts, or use a disperser, to avoid excessive water runoff during bad weather.

Jointing Product	Product code	Color	Size	Units per pallet
HP NextGel [™]	varies per color	See our website	50 lb (bag)	56



















LOCATIONS & CONTACT INFO

ASP ENTERPRISES

aspent.com

salesasp@aspent.com

St. Louis, MO 636.343.4357

Kansas City, MO 816.554.1191

402.861.8579 Wichita, KS

Omaha, NE

316.393.1554 970.535.0863

BOWMAN CONSTRUCTION SUPPLY

bowmanconstructionsupply.com

salesbcs@bowmanconstructionsupply.com salesquick@quicksupplyco.com

Denver, CO Colorado Springs, CO

303.696.8960 719.257.7840 Loveland, CO

OUICK SUPPLY CO.

quicksupplyco.com

Des Moines, IA 515.289.1271

CASCADE GEOSYNTHETICS

cascadegeos.com

salescascade@cascadegeos.com

Portland, OR 971.339.1020

SOLUTIONS WE SUPPLY

GEOSYNTHETICS

Filter Fabrics

Stabilization Fabrics

Geogrids

- Road Grids
- Wall Grids
- Slope Stabilization

Specialty Fabrics

Composite Geomembranes

• GCLs, PVC, HDPE, LLDPE, EPDM, Granular Bentonite

SEDIMENT CONTROL

Inlet Protection

· Grated Inlet, Curb Inlet, Area Inlet Protection

Ditch Checks

- · Triangle Silt Dike
- GeoRidge

Perimeter Protection

- · High and Low-Porosity Silt Fence, Straw Wattles, Silt Socks
- Safety Fence

Flocculants & Water Treatment

Polymer-Based & Natural Flocculants

Sediment Basin Skimmers

Dewatering Bags

Trackout Control

- FODS
- Rumble Grates

Turbidity Curtains

EROSION CONTROL

Basic Hydraulically Applied Mulches

- Wood
- Paper
- Blends
- Straw

High-Performance Hydraulically Applied Products

- FGM
- Additives & Tackifiers

Temporary Erosion Control Blankets

- Coir & Jute Mat/Nettings
- Short-Term ECBs
- Extended-Term ECBs

Permanent Erosion Control Blankets

- Turf Reinforcement Mats
- HP-TRMs
- Anchor Reinforced Vegetation System

Structural BMPs

- Transition Mats
- Geoweb Cellular Confinement
- Composite Vegetated Armor System
- Flex MSE Vegetated Wall System
- Articulated Concrete Block
- Gabions
- · Grout-Filled Geotextile Mats

Vegetation Establishment

- · Native Seed & Turf Seed
- Fertilizers
- · Organic Soil Additives
- Stratavault Soil Cells

STORMWATER MANAGEMENT

Water Quality

- Inlet Filter Boxes
- Pre-Treatment Chamber
- Nutrient Separating Baffle Boxes
- · High-Flow Biofiltration Media
- · Hydrodynamic Separators
- Stratavault

Water Ouantity

- · Modular Underground Storage Systems
- Chamber Detention Systems

Drainage

- HDPE Swale Liner
- Pipe & Fittings
- · Drainage Composites
- Strip Drain

Inlet Structures

- PVC
- · Drain Basins, In-Line Drains
- Landscape

Permeable Pavers

- Permeable Articulating Concrete Block
- Grass Pavers
- · Gravel Pavers
- Concrete Pavers

SPECIALTY

Natural & Synthetic Coir Fiber Logs **Vegetated Reinforced Soil Slopes** Soil Anchors **Root Barrier System** AquaBlok Muscle Wall

We are full line distributors of construction materials for all project types. Contact us for assistance with a project. From specification and development to installation and completion, we're here to help with all of your site solution needs.