



ProMatrix®

SDS Number: CON069

Revision Date: 1/1/17

Page 1 of 6

1 PRODUCT AND COMPANY IDENTIFICATION**Manufacturer**

PROFILE Products, LLC
750 LAKE COOK ROAD
SUITE 440
BUFFALO GROVE, IL 60089

Emergency: Emergency Phone: (800) 424-9300 (ChemTrec)
Contact: ChemTrec Acct #: CCN792719
Phone: (847) 215-1144
Fax: (847) 215-0577
Email: tech@profileproducts.com
Web: www.profileproducts.com

Product Name: ProMatrix®
Revision Date: 1/1/17
SDS Number: CON069
CAS Number: Not applicable
Product Use: Erosion control and revegetation mulch for hydraulic seeding

Product Description: Green dyed wood fibers, biodegradable fibers, minerals and a proprietary binder mixture.

2 HAZARDS IDENTIFICATION**Classification of the Substance or Mixture**

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

No GHS Classifications Indicated

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **NONE**

no GHS pictograms indicated for this product

GHS Hazard Statements:

no GHS hazards statements indicated

GHS Precautionary Statements:

no GHS precautionary statements indicated

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Inhalation, skin contact, eye contact

Inhalation: Wood may cause sneezing, irritation, and dryness of the nose and throat. Dust may aggravate pre-existing respiratory conditions.

Skin Contact: Wood dust can cause irritation. Skin absorption is not known to occur.

Eye Contact: Wood dust can irritate the eyes.

Ingestion: No reports of human ingestion.

OSHA Classification: Wood dust is a hazardous substance as defined by the Hazard Communication Standard 29CFR 1910.1200


ProMatrix®

SDS Number: CON069

Revision Date: 1/1/17

Page 2 of 6

NFPA: Health = 1, Fire = 1, Reactivity = 0, Specific Hazard = n/a



3 COMPOSITION/INFORMATION OF INGREDIENTS

Ingredients:

Cas#	%	Chemical Name
0	Proprietary	Hydrocolloidal Based Polysaccharide Tackifier
9000300	Proprietary	Guar Gum

4 FIRST AID MEASURES

- Inhalation:** Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation persists. In high dust levels wear dust mask.
- Skin Contact:** Usually not a problem. Wash off with running water if irritation is experienced.
- Eye Contact:** Open eyelids and flush with water.
- Ingestion:** Get medical attention.

5 FIRE FIGHTING MEASURES

- Flammability:** Combustible product
 - Flash Point:** Not applicable
 - Flash Point Method:** Not applicable
 - Autoignition Temp:** 200-260°C (400-500°F)
- Conditions to avoid: In contact with flames or hot surfaces
 Flammable- Extinguish with water; same as a wood fire

6 ACCIDENTAL RELEASE MEASURES

Scoop up product. Wear goggles and respirator if dust is produced in unventilated areas. Wet product will be slippery.

7 HANDLING AND STORAGE

- Handling Precautions:** Clean up areas where dust settles. Minimize blowdown or other practices that generate high airborne dust concentrations.
- Storage Requirements:** Store in a cool, dry place. Keep away from sources of ignition.



ProMatrix®

SDS Number: CON069

Revision Date: 1/1/17

Page 3 of 6

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: None required for outdoor mixing and application. Use dust collection system for indoor handling operations.
Personal Protective Equipment: Eye Protection: Wear goggles when emptying bags and during other operations where there is a risk of dust entering the eyes.
Gloves: Leather, plastic or rubber gloves could be worn to minimize skin irritation.
Respirators: When handling methods generate dust at concentrations that exceed occupational exposure limits, wear a NIOSH approved respirator. A fabric respirator or a facepiece respirator with dust cartridges will generally provide adequate protection.
Footwear: The product is slippery when wet. Wear appropriate footwear.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Dyed green wood fibers - Pine & mixed hardwoods
Physical State: Wood Fibers Odor: Mild wood odor
Spec Grav./Density: Lighter than water
Vapor Pressure: N/A

10 STABILITY AND REACTIVITY

Chemical Stability: Stable product
Conditions to Avoid: Contact with strong acids and oxidizers may generate heat. Product may ignite at temperatures in excess of 200°C (400°F).
Materials to Avoid: Strong acids and oxidizers
Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

EFFECTS OF CHRONIC EXPOSURE:
Inhalation: Frequent and repeated exposure to wood dust is associated with an increased risk of developing nasal cancer.
Skin Contact: Although rare, wood dust may cause dermatitis in sensitized people.
Occupational Exposure Limits:
Wood dusts- All other species: ACGIH (2007): TLV-TWA 1 mg/m³ (Inhalable fraction); A4
Particulates Not Otherwise Regulated (PNOR): OSHA: PEL-TWA 15 mg/m³ (Total Dust); 5 mg/m³ (Respirable fraction)
Irritancy: Wood dust is a mild irritant
Sensitization: Some wood dusts may cause allergic skin reactions



ProMatrix®

SDS Number: CON069

Revision Date: 1/1/17

Page 4 of 6

12

ECOLOGICAL INFORMATION

Guar Gum (CAS# 9000-30-0) is listed as an inert ingredient permitted for use in nonfood use pesticide products by EPA. It is also classified under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA) as a minimal risk inert substance (List 4A) meaning that as a pesticide, Guar Gum is considered by the EPA to pose little or no risk to humans or the environment. The US Department of Agriculture (USDA) National Organic Program (NOP) also allows the use of Guar Gum in a variety of applications, but primarily as a pesticide in organic production operations. Finally, Guar Gum is listed on the Generally Recognized as Safe (GRAS) list by the Food and Drug Administration (FDA).

48-hr LC₅₀ = >100% for *Daphnia magna* when runoff generated using ASTM D7101 (2"/hr rainfall rate) was tested according to EPA-821-R-02-012.

13

DISPOSAL CONSIDERATIONS

Normally can be disposed of as a wood residue. Ensure disposal is in compliance with local, provincial (state), and federal regulations.

14

TRANSPORT INFORMATION



ProMatrix®

SDS Number: CON069

Revision Date: 1/1/17

Page 5 of 6

15	REGULATORY INFORMATION
----	-------------------------------

Component (CAS#) [%] - CODES

Hydrocolloidal Based Polysaccharide Tackifier (0) [Proprietary]

Guar Gum (9000300) [Proprietary] TSCA

Regulatory CODE Descriptions

TSCA = Toxic Substances Control Act

COMPONENT / (CAS/PERC) / CODES

*Guar gum (9000300 n/a%) TSCA

REGULATORY KEY DESCRIPTIONS

- MASS = MA Massachusetts Hazardous Substances List
- NRC = Nationally Recognized Carcinogens
- OSHAWAC = OSHA Workplace Air Contaminants
- PA = PA Right-To-Know List of Hazardous Substances
- TXAIR = TX Air Contaminants with Health Effects Screening Level

- CERCLA = Superfund clean up substance
- CSWHS = Clean Water Act Hazardous substances
- EHS302 = Extremely Hazardous Substance
- EPCRAWPC = EPCRA Water Priority Chemicals
- HAP = Hazardous Air Pollutants
- NJEHS = NJ Extraordinarily Hazardous Substances
- NJHS = NJ Right-to-Know Hazardous Substances
- OSHAPSM = OSHA Chemicals Requiring process safety management
- SARA313 = SARA 313 Title III Toxic Chemicals

TSCA = Toxic Substances Control Act



Solutions for your Environment™

SDS

GHS Safety Data Sheet

PROFILE Products, LLC

ProMatrix®

SDS Number: CON069

Revision Date: 1/1/17

Page 6 of 6

16

OTHER INFORMATION

Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).



DISTRIBUTED BY:

ASP Enterprises, Quick Supply Co., Bowman Construction Supply & Cascade Geosynthetics are sister companies that serve customers from the Midwest, across the Rocky Mountains to the Pacific Northwest. Together we supply customers with a variety of environmental construction materials including erosion and sediment control, geosynthetics, stormwater management, drainage products, hardscapes and outdoor living, revegetation and soil amendments, waterproofing solutions and more.



We are full line distributors of environmental construction materials for all project types. Contact us for assistance with a project or a quote on products. From specification recommendations and project development to installation and completion, we're here to help with all of your site solution needs. Our warehouses are stocked with readily available inventory and we offer same and next-day deliveries.

ASP ENTERPRISES

aspent.com

salesasp@aspent.com

ST. LOUIS

1099 Cassens Industrial Ct.
St. Louis, MO 63026
636-343-4357

KANSAS CITY

5301 E 59th St.
Kansas City, MO 64130
816-554-1191

OMAHA

15263 Cooper St.
Omaha, NE 68138
402-861-8579

WICHITA

316-393-1554

WENTZVILLE

1906 E Service Rd. HWY 61 N
Wentzville, MO 63385
636-445-9090

QUICK SUPPLY CO.

quicksupplyco.com

salesquick@quicksupplyco.com

DES MOINES

6620 NW Toni Dr.
Des Moines, IA 50313
515-289-1271

BOWMAN CONSTRUCTION SUPPLY

bowmanconstructionsupply.com

salesbcs@bowmanconstructionsupply.com

DENVER

10801 E. 54th Ave.
Denver, CO 80239
303-696-8960

COLORADO SPRINGS

2445 Wayside Ct.
Colorado Springs, CO 80915
719-257-7840

LOVELAND

4495 Woods Ave.
Loveland, CO 80538
970-535-0863

CASCADE GEOSYNTHETICS

cascadageos.com

salescascade@cascadageos.com

PORTLAND

3610 N. Suttle Rd. Bldg B
Portland, OR 97217
971-339-1020

SALT LAKE CITY

425 N. Neil Armstrong Rd.
Salt Lake City, UT 84116
435-276-0820

**GEOSYNTHETICS | EROSION CONTROL | STORMWATER MANAGEMENT
REVEGETATION & SOIL AMENDMENTS | SEDIMENT CONTROL | HARDSCAPES**