

# RIVERCREST® WALL

**UNILOCK®**

TECH SHEET

**THICKNESS** 114MM  
**REGION** CHICAGO



APPLICATIONS

Note: Not all sizes are suitable for every application. Contact Unilock Representative for assistance.

Fire Feature	Garden Wall
Outdoor Kitchen	Pillars
Retaining Wall	Seat Wall
Water Features	

COLORS

BUFF  
FINISH: FLAGSTONE

JUMPER UNIT 1 200mm x 114mm x 240mm 7 7/8" x 4 1/2" x 9 1/2"	JUMPER UNIT 2/3 310mm x 114mm x 240mm 12 1/4" x 4 1/2" x 9 1/2"
JUMPER UNIT 4 420mm x 114mm x 240mm 16 5/8" x 4 1/2" x 9 1/2"	CORNER JUMPER 450mm x 114mm x 240mm 17 3/4" x 4 1/2" x 9 1/2"
PILLAR UNIT 20"X20" 500mm x 114mm x 500mm 19 3/4" x 4 1/2" x 19 3/4"	WALL RADIUS 1,060mm x 114mm x 225mm 41 3/4" x 4 1/2" x 8 7/8"

COASTAL SLATE  
FINISH: FLAGSTONE

JUMPER UNIT 1  
200mm x 114mm x 240mm  
7 7/8" x 4 1/2" x 9 1/2"

JUMPER UNIT 2/3  
310mm x 114mm x 240mm  
12 1/4" x 4 1/2" x 9 1/2"

JUMPER UNIT 4  
420mm x 114mm x 240mm  
16 5/8" x 4 1/2" x 9 1/2"

CORNER JUMPER  
450mm x 114mm x 240mm  
17 3/4" x 4 1/2" x 9 1/2"

PILLAR UNIT 20"X20"  
500mm x 114mm x 500mm  
19 3/4" x 4 1/2" x 19 3/4"

WALL RADIUS  
1,060mm x 114mm x 225mm  
41 3/4" x 4 1/2" x 8 7/8"

**TYPICAL CROSS SECTION**

Note: Base, screed bed, infill aggregates and or reinforcements may vary based on project requirements or as specified by engineer.

---

PACKAGING

	(57) RANDOM RANDOM BUNDLE	(57) CORNER RANDOM BUNDLE	(114) RANDOM JUMPER RANDOM BUNDLE	CORNER JUMPER	PILLAR UNIT 20"X20"	WALL RADIUS
UNIT THICKNESS (MM)	57	57	114	114	114	114
LAYERS PER BUNDLE	8	4	4	2	4	4
FCFT PER BUNDLE	24.30	16.21	13.73	13.55	-	-
FCFT PER LAYER	3.04	4.05	3.43	6.77	-	-
FCFT PER UNIT	0.19	0.41	0.34	0.85	-	-
UNITS PER BUNDLE	128	40	40	16	8	12
UNITS PER LAYER	16	10	10	8	2	3
LBS PER BUNDLE	1,990	1,173	1,631.06	972.85	1,763.68	1,402.13
LBS PER LAYER	248.75	293.25	407.76	486.42	440.92	350.53
LBS PER UNIT	15.55	29.33	40.78	60.80	220.46	116.84

## INSTALLATION NOTES

---

Rivercrest Wall is a unique residential and commercial landscape wall block featuring a water-worn ledgerstone appearance. The special integrated alignment system makes installation simple and painless for the professional landscaper or DIY. The unique shape and array of unit sizes & textures allows you to create virtually any shape or pattern you desire.

Applications – Design and build projects such as planters, steps, grill islands, pillars, seat walls and water features. Can be used for straight and curved installations (Radius 5' is the tightest radius).

Capacity – Gravity walls up to 24" (60cm). Geogrid reinforced walls up to 6 ft. (1.8m).

Recommended Base Stabilization – one layer of DriveGrid™ stabilization grid between subgrade and base material. Use under Standard Base or Permeable Base.

Standard Base – Min. 6" – 8" of ¾" Crusher Run gravel (any road base standard in accordance with ASTM-D2940) compacted to 98% Standard Proctor Density (SPD).

Alternative Permeable Base – Min. 6" – 8" of ¾" clear open-graded stone compacted to achieve full particle lock-up and consolidation. (Clear open-graded does not compact but does consolidate slightly by rattling the particles together.)

Leveling – Leveling retaining wall blocks directly on top of gravel is tedious and generally does not yield the best results. U-Grip Base units or universal base pads are recommended under all Unilock walls for improved accuracy and speedier installation. Additional benefits include long term structural integrity and an overall better appearance. Poured concrete leveling pads, reinforced with rebar, are also a great way to accomplish leveling, particularly for larger installations. You must ensure that the concrete is poured and finished perfectly in order to achieve a good visual appearance.

Connection – features a unique integrated alignment connection. Use appropriate concrete adhesive for connection between units where required. Always read adhesive manufacturers' directions prior to gluing.

Handling – No specific handling instructions.

Coping - This wall requires coping. Choose Rivercrest Coping or any of our natural stone coping options. Install with tight joints or 3/16" gap between units and amend with an exterior latex caulking. Cutting may be required; a diamond blade saw is required to cut coping properly. Glue all coping using a specially formulated concrete adhesive that is strong and will not break down over time. Always read adhesive manufacturers' directions prior to gluing.

---

Contact Unilock Representative for actual color samples and availability. Unilock reserves the right to change product information without notice.

PDF Generated September 25, 2025, 10:23 am



**Bowman**  
Construction  
Supply Inc.



**Quick**  
Supply Co.



**Cascade**  
GEOSYNTHETICS

## LOCATIONS & CONTACT INFO

### ASP ENTERPRISES

aspent.com  
salesasp@aspent.com

### BOWMAN CONSTRUCTION SUPPLY

bowmanconstructionsupply.com  
salesbcs@bowmanconstructionsupply.com

### QUICK SUPPLY CO.

quicksupplyco.com  
salesquick@quicksupplyco.com

### CASCADE GEOSYNTHETICS

cascadegeos.com  
salescascade@cascadegeos.com

**St. Louis, MO** 636.343.4357  
**Omaha, NE** 402.861.8579  
**Kansas City, MO** 816.554.1191  
**Wichita, KS** 316.393.1554

**Denver, CO** 303.696.8960  
**Colorado Springs, CO** 719.257.7840  
**Loveland, CO** 970.535.0863

**Des Moines, IA**  
515.289.1271

**Portland, OR**  
971.339.1020

## SOLUTIONS WE SUPPLY

### GEOSYNTHETICS

Filter Fabrics

Stabilization Fabrics

Geogrids

- Road Grids
- Wall Grids
- Slope Stabilization

Specialty Fabrics

Composite Geomembranes

- GCLs, PVC, HDPE, LLDPE, EPDM, Granular Bentonite

### SEDIMENT CONTROL

Inlet Protection

- Grated Inlet, Curb Inlet, Area Inlet Protection

Ditch Checks

- Triangle Silt Dike
- GeoRidge

Perimeter Protection

- High and Low-Porosity Silt Fence, Straw Wattles, Silt Socks
- Safety Fence

Flocculants & Water Treatment

- Polymer-Based & Natural Flocculants

Sediment Basin Skimmers

Dewatering Bags

Trackout Control

- FODS
- Rumble Grates

Turbidity Curtains

### EROSION CONTROL

Basic Hydraulically Applied Mulches

- Wood
- Paper
- Blends
- Straw

High-Performance Hydraulically

Applied Products

- BFM
- FGM
- Additives & Tackifiers

Temporary Erosion Control Blankets

- Coir & Jute Mat/Nettings
- Short-Term ECBs
- Extended-Term ECBs

Permanent Erosion Control Blankets

- Turf Reinforcement Mats
- HP-TRMs
- Anchor Reinforced Vegetation System

Structural BMPs

- Transition Mats
- Geoweb Cellular Confinement
- Composite Vegetated Armor System
- Flex MSE Vegetated Wall System
- Articulated Concrete Block
- Gabions
- Grout-Filled Geotextile Mats

Vegetation Establishment

- Native Seed & Turf Seed
- Fertilizers
- Organic Soil Additives
- Stratavault Soil Cells

### STORMWATER MANAGEMENT

Water Quality

- Inlet Filter Boxes
- Pre-Treatment Chamber
- Nutrient Separating Baffle Boxes
- High-Flow Biofiltration Media
- Hydrodynamic Separators
- Stratavault

Water Quantity

- Modular Underground Storage Systems
- Chamber Detention Systems

Drainage

- HDPE Swale Liner
- Pipe & Fittings
- Drainage Composites
- Strip Drain

Inlet Structures

- PVC
- Drain Basins, In-Line Drains
- Landscape

Permeable Pavers

- Permeable Articulating Concrete Block
- Grass Pavers
- Gravel Pavers
- Concrete Pavers

### SPECIALTY

Natural & Synthetic Coir Fiber Logs

Vegetated Reinforced Soil Slopes

Soil Anchors

Root Barrier System

AquaBlok

Muscle Wall

We are full line distributors of construction materials for all project types. Contact us for assistance with a project. From specification and development to installation and completion, we're here to help with all of your site solution needs.

**GEOSYNTHETICS | EROSION CONTROL | STORMWATER MANAGEMENT  
SEDIMENT CONTROL | REVEGETATION & SOIL AMENDMENTS**