

MATERIAL PROPERTY DATA SHEET




EXCEL PP5-Xtreme™

Permanent • 3-D Woven • UV Stable •
High Performance Turf Reinforcement Mat

DESCRIPTION

PP5-Xtreme is a High-Performance Turf Reinforcement Mat (HP-TRM) produced by weaving 100% UV-stabilized, high denier synthetic mono-filament yarns woven into permanent, high-strength, three-dimensional structure. The optimized properties of the material provide immediate erosion control with excellent vegetation establishment and class-leading long-term turf reinforcement. Additionally, the high strength at low elongation is ideal for slope stability applications (when paired with deep-seated, high strength anchors) and is unique compared to other HPTRMs. The design life of PP5-Xtreme is rated at fifty years in typical installations, however, can vary based on conditions. PP5-Xtreme is made in the USA and monitored by quality assurance testing at a GAI-LAP accredited laboratory.



Material Content	
Woven , Single Layer	Green or Tan

Standard Roll Sizes			
Width	8 ft (2.4 m)	15 ft (4.5 m)	
Length	135 ft (40.5 m)	150 ft (45 m)	
Weight ± 10%	90 lb (42.0 kg)	113 lb (51.0 kg)	
Area	120 sy (100 m ²)	250 SY (209 m ²)	

Material available in custom roll sizes

Approvals & Classification	
Classification	FHWA: Type 5.C / ECTC: 5.F
TTI Approvals	N/A
NTPEP Number	ECP-2022-01-014

Disclaimer: The information contained herein may represent product index data, performance ratings, bench scale testing or other material utility quantifications. Each representation may have unique utility and limitations. Every effort has been made to ensure accuracy, however, no warranty is claimed and no liability shall be assumed by Western Green or its affiliates regarding the completeness, accuracy or fitness of these values for any particular application or interpretation. While testing methods are provided for reference, values shown may be derived from interpolation or adjustment to be representative of intended use. For further information, please feel free to contact Western Green.

©2022, Western Excelsior is a registered trademark from Western Green. Certain products and/or applications described or illustrated herein are protected under one or more U.S. patents. Other U.S. patents are pending, and certain foreign patents and patent applications may also exist. Trademark rights also apply as indicated herein. Final determination of the suitability of any information or material for the use contemplated, and its manner of use, is the sole responsibility of the user. Printed in the U.S.A.

Rev. 4.2023

Scan for additional and updated product information, or [click here](#).



Index Property	Test Method	MARV	
Thickness	ASTM D6525	0.3 in.	(7 mm)
Mass/Unit Area	ASTM D6566	9.0 oz/sy	(300 g/sm)
Tensile Strength – MD	ASTM D6818	4,000 lbs/ft	(58.4 kN/m)
Tensile Strength – TD	ASTM D6818	3,000 lbs/ft	(43.8 kN/m)
Elongation - MD	ASTM D6818	25%	
Elongation – TD	ASTM D6818	20%	
UV Stability	ASTM D4355	90% @6000 hr	
UV Stability	ASTM D7238	90% @6000 hr	
Resiliency	ASTM D6524	75%	
Light Penetration	ASTM D6567	30%	
Biomass Improvement	ASTM D7322	325%	
Specific Gravity	ASTM D792	57.4 lb/ft ³	(0.92 g/cm ³)
Porosity	ECTC	95%	
Carbon Footprint	GHG*	1.6 kg CO ₂ e/m ²	

Design Parameters		
Property	Unvegetated	Vegetated ³
RUSLE C Factor ²	N/A	N/A
Slope Maximum Gradient ¹	0.5H:1V	0.5H:1V
Permissible Shear Stress ²	2.3 psf	17.0 psf (815 Pa)
Permissible Velocity ²	8.0 fps	25.0 fps (7.6 m/s)
τ_{veg} / τ_{TRM} (HEC-15)	N/A	0.26

Manning's n Roughness (HEC-15)		
τ_{lower}	τ_{mid}	τ_{upper}
0.027	0.027	0.025

¹ Maximum Gradient a recommendation for typical installations.

² Hydraulic thresholds compliant with ASTM D6459/D6460 but generalized for typical applications.

³ Vegetated values dependent on established stand of vegetation

*WRI/WBCSD Greenhouse Gas Protocol: Product Life Cycle Accounting and Reporting Standard, 2013.



DISTRIBUTED BY:

ASP Enterprises, Quick Supply Co., Bowman Construction Supply & Cascade Geosynthetics are sister companies that serve customers from the Midwest, across the Rocky Mountains to the Pacific Northwest. Together we supply customers with a variety of environmental construction materials including erosion and sediment control, geosynthetics, stormwater management, drainage products, hardscapes and outdoor living, revegetation and soil amendments, waterproofing solutions and more.



We are full line distributors of environmental construction materials for all project types. Contact us for assistance with a project or a quote on products. From specification recommendations and project development to installation and completion, we're here to help with all of your site solution needs. Our warehouses are stocked with readily available inventory and we offer same and next-day deliveries.

ASP ENTERPRISES

aspent.com

salesasp@aspent.com

ST. LOUIS

1099 Cassens Industrial Ct.
St. Louis, MO 63026
636-343-4357

KANSAS CITY

5301 E 59th St.
Kansas City, MO 64130
816-554-1191

OMAHA

15263 Cooper St.
Omaha, NE 68138
402-861-8579

WICHITA

316-393-1554

WENTZVILLE

1906 E Service Rd. HWY 61 N
Wentzville, MO 63385
636-445-9090

QUICK SUPPLY CO.

quicksupplyco.com

salesquick@quicksupplyco.com

DES MOINES

6620 NW Toni Dr.
Des Moines, IA 50313
515-289-1271

BOWMAN CONSTRUCTION SUPPLY

bowmanconstructionsupply.com

salesbcs@bowmanconstructionsupply.com

DENVER

10801 E. 54th Ave.
Denver, CO 80239
303-696-8960

COLORADO SPRINGS

2445 Wayside Ct.
Colorado Springs, CO 80915
719-257-7840

LOVELAND

4495 Woods Ave.
Loveland, CO 80538
970-535-0863

CASCADE GEOSYNTHETICS

cascadageos.com

salescascade@cascadageos.com

PORTLAND

3610 N. Suttle Rd. Bldg B
Portland, OR 97217
971-339-1020

SALT LAKE CITY

425 N. Neil Armstrong Rd.
Salt Lake City, UT 84116
435-276-0820

**GEOSYNTHETICS | EROSION CONTROL | STORMWATER MANAGEMENT
REVEGETATION & SOIL AMENDMENTS | SEDIMENT CONTROL | HARDSCAPES**